

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (canceled)

2. (currently amended) A compressor ~~as defined in claim 1~~, comprising:

a compression chamber for compressing working fluid within an inside

thereof;

a discharge port, through which the working fluid flows out from the

compression chamber;

a valve seat portion provided around the discharge port and having a tapered surface, so that a cross-sectional area of the discharge port increases in a direction away from the compression chamber;

a valve having a projection portion having a tapered surface, only a portion of which, in a closed position, is in contact with the tapered surface of the valve seat portion to form a line contact between the valve and the valve seat portion, wherein the valve has a flat surface portion provided at an end portion of the valve on the side of the compression chamber; and

a retainer for positioning the valve on the valve seat portion.

3. (currently amended) A compressor as defined in claim 2 4, wherein the discharge port has a cylindrical portion provided between the compression chamber and the valve seat portion.

Sub
C1
B1
4. (canceled)

5. (currently amended) A compressor, comprising:

a compression chamber including a cylinder and a piston for compressing working fluid therebetween;

an end plate for blocking an opening of the cylinder, the end plate including a discharge port provided therethrough, through which the working fluid flows out from the compression chamber;

a valve seat portion provided around the discharge port and having a tapered surface, so that a cross-sectional area of the discharge port increases in a direction away from the compression chamber;

a valve having a projection portion having a tapered surface, at least a portion of which, in a closed position is in contact with the tapered surface of the valve seat portion as defined in claim 4, wherein the valve has a flat surface portion provided at an end portion of the valve on the side of the compression chamber;

a bore provided the end plate, the bore being connected to the valve seat portion; and

a retainer inserted into the bore for holding the valve opposing to the valve seat portion.

6. (currently amended) A compressor as defined in claim 5 4, wherein the retainer through which the working fluid is discharged includes an opening.

Sub
C1

7. (currently amended) A compressor as defined in claim 5 4, wherein the discharge port has a cylindrical portion provided between the compression chamber and the discharge port with said valve seat portion.

B1

8. (currently amended) A compressor as defined in claim 5 4, further comprising a passage provided between the retainer and an inner side surface of the bore for conducting the working fluid therethrough.

9. (currently amended) A compressor, as defined in any one of the claims ~~1 to 8~~ 2, 3 and 5 to 8, further comprising:

a biasing means for supporting the valve, so that the valve is biased towards the closed position in contact with the tapered surface of said valve seat portion but can be forced out of contact with the tapered surface of the valve seat portion by pressure within the compression chamber.

10. (previously presented) A compressor, as defined in claim 9, wherein biasing means is a coiled spring engaged with the valve, the coiled spring being formed nearly into a conical shape.

11. (previously presented) A compressor, as defined in claim 9, wherein the biasing means is a leaf spring formed with slits for biasing the valve with a central portion thereof.

12. (canceled)

Sub
C1

13. (currently amended) A compressor ~~as defined in claim 1~~, comprising:
a compression chamber for compressing working fluid within an inside
thereof;

a discharge port, through which the working fluid flows out from the
compression chamber;

B1

a valve seat portion provided around the discharge port and having a tapered
surface, so that a cross-sectional area of the discharge port increases in a direction
away from the compression chamber;

a valve having a projection portion having a tapered surface, only a portion of
which, in a closed position, is in contact with the tapered surface of the valve seat
portion to form a line contact between the valve and the valve seat portion, wherein
the tapered surface of the projection portion of said valve has a conical portion at an
end closest to said compression chamber and a spherical portion adjacent the
conical portion, wherein, in a closed position, a portion of the spherical portion
contacts a portion of the tapered surface of said valve seat portion to form the line
contact between said valve and said valve seat portion; and

a retainer for positioning the valve on the valve seat portion.

14. (previously presented) A compressor as defined in claim 13, wherein the tapered
surface of the valve seat portion has a conical shape.

15. (currently amended) A compressor as defined in claim 5 ~~4~~, wherein the valve
seat portion and the bore are coaxial.

Sub
C1

16. (currently amended) A compressor as defined in claim 54, wherein the tapered surface of the projection portion of said valve has a conical portion at an end closest to said compression chamber and a spherical portion adjacent the conical portion, wherein, in a closed position, a portion of the spherical portion contacts a portion of the tapered surface of said valve seat portion to form the line contact between said valve and said valve seat portion.

B1

17. (previously presented) A compressor as defined in claim 16, wherein the tapered surface of the valve seat portion has a conical shape.